

FIELD BOSS™ XSTREAM

■ SFB060FG290EX ■ SFB100FG290EX



DESIGNED BETTER. BUILT STRONGER. LASTS LONGER.



SPRAY-COMMAND™ CONTROLS

Select where you want to spray and at what pressure with all controls mounted to the SWING-ARM™.

SWING-ARM™

All controls are at your fingertips and within reach from the UTV cab. Hoses are protected and out of sight.

QUICK-ATTACH™ BOOM BRACKETS

Built-in boom connection points to save time and hassle when removing and attaching a spray boom.



AUTO-DRAIN™ SUMP BASE

The sloped tank base channels every ounce of spray chemical to the drain. Just where it should go.

QUICK-CONNECT™ BOOM PORTS

Plumb a spray boom to this sprayer in seconds with three brass screw-on fittings. Zero tools needed.

TIME-SAVER™ FORK POINTS

The built-in fork slots make the entire unit a breeze to lift and load.

290
PSI

5.8
GPM

37'
VERTICAL
SPRAY

45'
HORIZONTAL
SPRAY



PRODUCT CODE	TANK SIZE (GAL)	DIMENSIONS (L X W X H)	MOTOR	PUMP	FLOW RATE (GPM)	PSI	HOSE LENGTH	SPRAY DISTANCE VERTICAL	SPRAY DISTANCE HORIZONTAL	DRY WEIGHT (LBS)
SFB060FG290EX	60	48" x 38" x 23"	GX120 Honda / 4 HP	Diaphragm	5.8	290	100'	37'	45'	185
SFB100FG290EX	100	48" x 45" x 27"	GX120 Honda / 4 HP	Diaphragm	5.8	290	100'	37'	45'	200

*Double your 5 yr tank warranty when you register this product. *All Enduraplas poly tanks are manufactured in the United States of America.



ENGINEERED FOR ENDURANCE®

www.enduraplas.com
info@enduraplas.com
1 (877) 877-4370